



Water disinfection

ND Water 2501 H

Areas for use:

- Drinking water quality for humans and animals
- Special designed for water up to 90°C

To be used at:	
Decentralized unit, for:	Water tanks in:
<ul style="list-style-type: none">• Factories production line water supply	<ul style="list-style-type: none">• Ships
<ul style="list-style-type: none">• Laboratory water supply	<ul style="list-style-type: none">• Trains
<ul style="list-style-type: none">• Food production water supply	<ul style="list-style-type: none">• Animal transportation
<ul style="list-style-type: none">• Breweries water supply	<ul style="list-style-type: none">• Any mobile water tank
Household's taps	Water trough

Available for 110-240 V.

Unit description:

The unit is made in stainless steel 1.4571 (316TI) with an inner bulb made of quartz glass, where the bulb is mounted into. This allows for replacement of bulb without turning of the water, during bulb change. All maintenance is done without tools. The unit has a high effectiveness in a very compact design, and with a low consumption of electricity.

The water runs through the lamp house and passes the quartz tube, where the UV bulb is placed. When the water passes the bulb, the disinfection takes place and all bacteria will be inactivated and the water will be safe.



The UV-Lamps:

The UV-lamps are known for long durability, high grade of disinfection and low energy consumption. The configuration of the unit allows for easy access to changing of the bulb and other maintenance.

The Lamps are designed for a lifetime of 8,000 hours

Technical data:

Type & mark	ND Water 2501 H		
Flow	21 m ³ /t		
UVC-Transmission	90% T ₁ cm	Life span on bulb	8.000 t
Water temperature	Up to 90°C	Dose	300 J/m ²
Housing	Stainless steel 1.4571 (316 TI)	Max allowed pressure	10 bar
Male thread size	R 1 1/2"	Type of housing	IP 65
Protection	FPM	Electric connection	110-240 V 50/60 Hz
Dimensions (L x Ø i mm)	928 x 85	Effect and fuse	106 W & 10 A
Flange distance	810 mm	Numbers of lamps	1
Weight	5,5 kg		

Accessories:

- Timer that count the operation hours of the lamp, in order to secure correct bulb change.
- UV-sensor for registration of proper operation when security is needed. The unit will signal (light) when intensity becomes too low.
- UV sensor for operating other equipment, delivers signal in mA
- High voltage able between the EVG and the lamp, 1 m, 5 m or 10 m
- Mounting set for easy mounting of unit on wall. Includes clamps for stainless unit and clamps for control box.
- Cleaning set for cleaning quartz glass. Special cloth and cleaning liquid.

Other products in the water family:

Single units for drinking water from 300 l to 4.000 l

Multiple for drinking water units from 4.000 l to 40.000 l

Units for:

- Process water
- Ponds
- Climate water
- Aquarium
- Fish ponds
- Pharmacy

UV radiation is dangerous for your skin and eyes! Both your eyes and skin must be appropriately protected from the direct UV light.

The user will be responsible for his own safety, as well as for the safety of people who are staying in areas where these units are being used. Please bear in mind that materials which are not UVC-resistant may be damaged.

Units for other use: Surface disinfection, air disinfection active and passive and Cleanboxes.