



CleanAccess – Air & UVC

Areas of use:

- Secure access without particles, bacteria, viruses and fungal spores.

For use in:	
• Cleanrooms	• Access sluices
• Production areas	• Bottling plants
• Stables	• Slaughterhouses
• Clean storage areas	

Unit description:

The sluice is built in stainless steel with two doors. The doors can only be opened individually, ensuring that no contamination can ever occur from one area to another.

A standard CleanAccess sluice comes with 12 pcs. UVC lamps to disinfect the item, as well as the air in the sluice.

The sluice come with emergency stop. When activated, the door opens to the unclean side.

CleanAccess is built to orders.



Technical data:

Type	CleanAccess (standard)		
Internal dimens. w,l,h	110 x 140 x 200 cm	Door	Swing door
External dimens. w,l,h	160 x 150 x 230 cm	Operating temperature	10°C to 40°C
Cargo size max	90 x 120 x 180 cm	Cabinet	Rustfri stål 304
UVC light for disinfect.	12 x 90W	Lifetime on bulbs	8.000 hours or 3 years
Nozzles/ blowers	24 nozzles, 2 blowers	Cleaning glass	Ones a year
Pre-filter & hepafilter	2/2	Service interval hepa	1/2 – 1 year
Emergency	4 pcs.	Connection	380 V, 16 amp
Processing time	60 sec. variable		

UV lamp:

UV lamps are known for a long durability, a high degree of disinfection and low energy consumption. The configuration of the unit allows easy access for bulb replacement and other maintenance. The lamps are designed for a lifetime of 8.000 hours or 3 years.

Other sluices:

- CleanAccess with air and UVC
- CleanAccess Cargo
- CleanBox 400, 600, 800

Units for other use: surface disinfection, water disinfection, air disinfection active and passive.

Warning:

UV radiation is dangerous for your skin and eyes! Both your eyes and skin must be appropriately protected from the direct UV light.

The user is responsible for his own safety, as well as for the safety of people who are staying in areas where these units are being used. Please bear in mind that materials which are not UVC-resistant may be damaged.
